

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 29.02.2016

Version number 2

Revision: 29.02.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name:

**Osmo Oil Stain**

Article number:

3501, 3512, 3514, 3516, 3518, 3519, 3541, 3543, 3564, 3590

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

advised against

No further relevant information available.

#### Application of the substance / the mixture

Priming

Coating compound/ Surface coating/ paint

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

 Osmo Holz und Color GmbH & Co. KG  
 Affhüppen Esch 12  
 D-48231 Warendorf

#### Further information obtainable from:

 Product safety department  
 Phone: +49 (0) 251 / 692 - 188  
 Fax: +49 (0) 251 / 692 - 462  
 e-mail: helmut.starp@osmo.de

#### 1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

#### 2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008

Void

Hazard pictograms

Void

Signal word

Void

Hazard statements

Void

Precautionary statements

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area.

P262 Do not get in eyes, on skin, or on clothing.

Additional information:

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.


Safety data sheet available on request.

(Contd. on page 2)

**Trade name: Osmo Oil Stain**

(Contd. of page 1)

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304	25-50%
EC number: 918-481-9			
Index number: 649-327-00-6			
Reg.nr.: 01-2119457273-39			

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

**After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:** If swallowed, seek medical advice immediately and show this container or label.**4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 29.02.2016

Version number 2

Revision: 29.02.2016

**Trade name: Osmo Oil Stain**

(Contd. of page 2)

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Ensure adequate ventilation  
Keep away from ignition sources.**6.2 Environmental precautions:**Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).**6.4 Reference to other sections**See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.**SECTION 7: Handling and storage****7.1 Precautions for safe handling**Keep away from heat and direct sunlight.  
Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**Store only in the original receptacle.  
Store in a cool location.**Information about storage in one common storage facility:**Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.**Further information about storage conditions:**Store in cool, dry conditions in well sealed receptacles.  
Keep container tightly sealed.**Storage class:**

10

(Contd. on page 4)

**Trade name: Osmo Oil Stain**

(Contd. of page 3)

7.3 *Specific end use(s)*

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

#### **8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m <sup>3</sup> , 150 ppm ppm
	Source: UK SIA

**Additional information:**

The lists valid during the making were used as basis.

#### **8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device only when aerosol or mist is formed.  
Short term filter device:  
Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

**Protection of hands:**

Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
To avoid skin problems reduce the wearing of gloves to the required minimum.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Goggles recommended during refilling

(Contd. on page 5)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 29.02.2016

Version number 2

Revision: 29.02.2016

**Trade name: Osmo Oil Stain****Body protection:** Protective work clothing

(Contd. of page 4)

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

**Form:** Viscous  
**Colour:** Different according to colouring  
**Odour:** Mild

**Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** > 180 °C

**Flash point:** > 60 °C (DIN 53213)**Ignition temperature:** 240 °C**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

**Lower:** 0.7 Vol %  
**Upper:** 6.0 Vol %

**Density at 20 °C:** 0.90 - 1.15 g/cm<sup>3</sup> (DIN 51757)**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Viscosity:**

**Dynamic:** Not determined.  
**Kinematic at 20 °C:** 30-45 s (DIN 53211/4 mm)

**Solvent content:****VOC (EC)** < 500 g/l (VOC-max. = 500 g/l (2010 A/i))**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity****10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

(Contd. on page 6)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 29.02.2016

Version number 2

Revision: 29.02.2016

**Trade name: Osmo Oil Stain**

(Contd. of page 5)

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

**10.4 Conditions to avoid**

No further relevant information available.

**10.5 Incompatible materials:**

No further relevant information available.

**10.6 Hazardous decomposition products:**Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****64742-48-9 aliphatic hydrocarbons, C10-C13**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

**Primary irritant effect:****Skin corrosion/irritation** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)

(Contd. on page 7)

**Trade name: Osmo Oil Stain**

(Contd. of page 6)

LC50 / 96h &gt; 1000 mg/l (fish) (OECD 203)

Biolog. Abbaubarkeit (-) (leicht abbaubar)

**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**European waste catalogue**

08 01 19\* aqueous suspensions containing paint or varnish containing organic solvents or other dangerous substances

15 01 10\* packaging containing residues of or contaminated by dangerous substances

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number****ADR, ADN, IMDG, IATA** Void**14.2 UN proper shipping name****ADR** Void**ADN, IMDG, IATA** Void**14.3 Transport hazard class(es)****ADR, ADN, IMDG, IATA****Class** Void**14.4 Packing group****ADR, IMDG, IATA** Void

(Contd. on page 8)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 29.02.2016

Version number 2

Revision: 29.02.2016

**Trade name: Osmo Oil Stain**

(Contd. of page 7)

<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
<b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****GISBAU-Code**

GISCODE: Ö60

**VOC (EC)**

&lt; 500 g/l (VOC-max. = 500 g/l (2010 A/i))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H304 May be fatal if swallowed and enters airways.

**Department issuing MSDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

**\* Data compared to the previous version altered.**